



POR-15® Restoration Products

POR-15 METAL MASK

Application Information

PRODUCT DESCRIPTION:

Metal Mask is a single component polyurethane coating that makes any metal surface look exactly like new bare metal. Metal Mask is non-porous and will not crack, chip, or peel when properly applied. It has great scratch and abrasion resistance and is not sensitive to UV light. Follow directions carefully and you will be rewarded with the finest protective coating for metal available anywhere!

Directions for Use:

For best results, when applying over bare metal, first prep your job with POR-15 Metal-Ready. Keep wet for 15 minutes, then wash off thoroughly with water and dry. Stir contents of can well, then apply Metal Mask with a foam brush. Try to avoid painting back and forth. Apply in thin, covering coats, using single, steady strokes to avoid flooding your job with too much paint, which could cause it to run and streak. Continue to stir Metal Mask so that metallic pigments remain in solution as you paint. Allow 3 or 4 days for Metal Mask to reach maximum hardness.

Spray Application:

Use 25 - 30 lbs(170-210Kpa). pressure for normal gloss. Use only POR-15 Solvent for thinning.

Precautions: Avoid skin contact. Remove from skin at once to avoid temporary staining. Use of protective gloves and ventilating equipment is recommended.

NOTE: Organic vapor particulate respirators, NIOSH/MSHA approved, must be used when spraying Metal Mask in a well-ventilated area. When spraying in an enclosed area, air-supplied respirator must be used. Moisture will shorten the life of unused Metal Mask. Seal can immediately after using. Keep out of reach of children. Harmful or fatal if swallowed. Use in well-ventilated areas only.

Hazardous ingredients: Oil modified polyurethane, Cas: Proprietary, Aliphatic hydrocarbon, Cas#64741-41-9, Aluminum, Cas#7429-90-5, Manganese Oxide, Cas#1313-13-9, Iron Oxide, Cas#1309-37-1, Silicon Dioxide, Cas#7631-86-9, Aluminum Dioxide, Cas#1344-28-1

Information contained herein is to our knowledge true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of its use are beyond our control, RestoMotive Laboratories/POR-15, Inc. disclaims any liability incurred in connection with the use of its products and information contained herein. No person is authorized or empowered to make any statement or recommendation not contained herein, and any such statement or recommendation so made shall not bind the Corporation. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patents.